



LED RETROFIT 6" RECESSED DISK LIGHT

Project Name:	
Catalog #:	
Fixture Type:	
Notes:	





PRODUCT DESCRIPTION:

120V LED disk light provides surface mount light for most A Series construction. It fits most 6 inch junction boxes and can replace 5 inch recessed can lights to eliminate baffles. B Input Voltage And it is suitable for use in dry, damp locations indoor/ 120V outdoor enclosed applications.

FEATURES:

- 120V 60Hz AC operation
- Dimmable 15W 28pcs LED chips
- Non-Dimmable Light source lumens: 1500; Fixture lumens: 1076
- DM Dimmable Translucent white PC opal diffuser
- Two mounting screws
- LED Available Philips screw driver sold separately
- ENERGY STAR
- 2-Year limited warranty

DIMENSIONS:



This fixture can be surface or recessed mounted:

Steps for Surface Mounting:

Before installation, please set two screws in the junction box and do not drive screws to the end of the junction box. Plug the white wire from the junction box to the driver white wire connector and plug the black wire to the black wire connector of the driver. Then attach the disk light to the junction box. Plug the grounding wire to the ground connector of the driver. Drive the screw to the end and make the disk light tightly fix on the junction box. Finally, twist diffuser on the disk light metal enclosure and lock the diffuser in place.

Steps for Recessed Mounting:

Make sure to release E26 lamp base inside can to be replaced by UL listed E26 base adapter and find white and black plug from E26 base adapter. To use wire plug to connect white socket of the LED driver. And connect driver grounding wire in the can grounding screw. Then squeeze the springs of LED disk light to be inserted into the can and it can be done one by one for both sides. To make sure to hook them on the disk light should be pushed on the surface of the can to make sure that the disk light is attached to the ceiling surface. And then twist the diffuser, which should be locked in the disk metal enclosure and keep the diffuser in place of the disk light surface.

ORDERING GUIDE:

Typical order example: ION-BL6-277DIMM-CREE-30K

ION-BL6	-		-		-	
ION	-	INPUT V	DIMMABLE		LED AVAILABLE	COLOR TEMP
		277 = 277V	= NON		CREE	30K = 3000K
		U = 120-277V	DIMM = Dimmable		CITIZEN	40K = 4000K
					EPISTAR	50K = 5000K
					SEOUL	
					OSRAM	

